



CRITICAL DIMENSIONS					
Α	В	С	D	Е	
6"	4"	2"	1 ½"	1 ½"	

NOTES:

- 1. On all streets with posted speeds of 25 mph or less, new street name letters shall be 4-inches tall.
- 2. Letter styles from the Standard Alphabets for Highway Signs Manual shall be as follows:
 - a. For the name of street use 4-inch series 'C'. Series 'B' is allowable for long names.
 - b. For numbered streets use 4-inch series 'D' for the number and 2-inch series 'C' for the suffix.
 - c. For prefixes, suffixes and block numbers use 2-inch series 'C'.
- 3. All signs shall include block numbers, as assigned by the *City*. Number streets shall include block numbers only when they differ from the actual street number.
- 4. Flat blanks for 4-inch street name signs shall be 0.100-inch gauge with 6063 T6 alodine coated aluminum substrate.
- 5. The minimum length shall be 24-inches and the maximum length shall be 36-inches, in 6-inch increments, with 1/2-inch radius corners.
- 6. Both sides of street name signs shall be green *3M Scotchlite* brand High Intensity Reflective sheeting.
- 7. All letters, numbers and borders shall be silver *3M Scotchlite* brand High Intensity Reflective sheeting.
- 8. Mounting hardware shall be 5½-inch #850F-long square caps for 2-inch square posts and #850F-long 90° crosspieces. For post mounting assembly see *Beaverton Standard Dwg* 400.



ENGINEERING DEPARTMENT

STREET NAME SIGN - 4 INCH

TRAFFIC ENGINEER	DATE	DRAWN BY	DRAWING NO.
Randall R. Wooley	6 - 10 - 04	JR - TD	410